

RAMPS &

BUILDING PERMIT

A building permit is required **before** construction begins.

CONTRACTOR LICENSING

All contractors who work in the Village must be licensed.

Information to be submitted when applying for permit:

L.	A plat of survey or accepted equivalent.
2.	Indicate location and dimensions of all existing structures on plat.
3.	Indicate location and all dimensions of the ramp.
4.	Footing depth and post sizes or post anchoring device.
5.	Deck lumber sizes and spans.
6.	Dimensions of handrails including spindle spacing.

Landing Required:

A minimum 3 foot-by-3 foot landing shall be provided at the top & bottom of ramps;
where doors open onto ramps; and where ramps change direction.

Ramp Width:

- Ramps shall not be less than 36 inches in clear width at all points between permitted hand rails. Ramps which change direction 90 degrees require a 36" landing.
- Ramps that change direction 180 degrees require a 48" landing.

Headroom:

• The minimum headroom in all parts of the ramp shall not be less than 6 feet, 8 inches measured vertically from the ramp landing or platform.

Ramp Slope:

- The maximum slope allowed is 1 unit vertical in 12 units horizontally.
- A steeper slope of 1 in 8 is allowed where 1 in 12 is impossible due to site constraints.

Ramp Length (Commercial only):

• The maximum rise allowed on any individual ramp is thirty inches (30").

Handrails:

- Handrails are required on at least one side of a ramp that exceeds a slope of 1 in 12, or on any areas above 30 inches in height from the grade below.
- Handrail height shall be between 34" and 38" as measured vertically from the ramp.
- Required handrails shall have balusters or ornamental closures which do not allow the passage of a sphere 4" or more in diameter.